

NEW ZEALAND

Engineering

THE JOURNAL
OF THE NEW ZEALAND INSTITUTION OF ENGINEERS



NIMBUS



An outstanding new pump built to the ISO International and metric standards

NIMBUS — a new metric range of standard, single entry, general purpose pumps, manufactured to ISO/DIS 2858 and DIN 24255 dimensions, with a single mechanical and hydraulic concept, but having a comprehensive coverage of duties in output and head.

Capacities range up to 1000m³/h (4000g.p.m. approx), and heads up to 120 metres (400 ft approx). The hydraulic design of the impellers is a product of the latest research and technology, combining maximum efficiency with good suction performance.

Shrouded impellers are employed, having balance holes to relieve pressure in the area of the gland/seal, and to reduce the hydraulic end thrust. Close grained cast iron is the material which will normally be used for the impellers, but the alternative of gunmetal is available for certain applications.

Nimbus pumps are of back pull-out design and can be dismantled without disturbing the pipework or motor when used with a spacer coupling, thereby reducing maintenance time.

One of the principal features of this new design is that twenty seven hydraulic units can be fitted to three basic bearing assemblies, a clear indication of the degree of standardisation that has been achieved.

Nimbus pumps can be used for most pumping applications where large solids are not present. Liquids able to be pumped range from water of varying purity in domestic water supplies, drainage, irrigation, and general circulation duties in industry and agriculture, to oil, chemicals and petroleum products.

Nimbus pumps are manufactured by Brown Brothers Engineers Ltd of Christchurch, to the design of Allen Gwynnes Pumps Ltd, of Bedford, England.

NIMBUS

For further information and technical data contact:

Brown Brothers Engineers Limited
Pumps Division

Christchurch:
P.O. Box 548
Phone 50-279
Telex NZ4941

Auckland:
P.O. Box 38-228
Phone 567-417
or 566-922

Lower Hutt:
P.O. Box 30-733
Phone 677-868



NEW ZEALAND

Engineering

VOL. 34, No. 9 : 15 SEPTEMBER 1979

The journal of

THE N.Z. INSTITUTION OF ENGINEERS, Fourth Floor,
Molesworth House, 101 Molesworth Street, P.O. Box
12-241, Wellington 1.

President, D. A. THOM, C.ENG., F.I.C.E., F.N.Z.I.E.

Secretary, A. J. BARTLETT, M.A. (OXON)

Designed for

The New Zealand engineer and planned to cover all
aspects of professional engineering. This journal is
received by all members of the N.Z. Institution of
Engineers.

Opinions expressed in the journal are not necessarily
those of the Institution or of the publishers.

Published monthly by

TECHNICAL PUBLICATIONS LTD., 127 Molesworth
Street, P.O. Box 3047, Wellington, N.Z. Telephone:
735-739. Telegrams: Tecpub.

Managing Editor

F. N. STACE, B.E.(ELECT. MECH.), B.E.(MECH.), C.ENG.,
F.I.E.E., F.I.S.T.C., M.I.E.E.E., M.N.Z.I.E.

Sub-Editor

V. J. WILSON, B.A., DIP. JOURN., HON. M.N.Z.A.S.C.

Advertisement Manager

P. D. DOILE

Business Manager

A. M. TEMPLE

Auckland Representative

R. M. (BOB) LITTLE, Dyllit Media Ltd, 24 Platina
Street, Remuera, Auckland 5. P.O. Box 28-372.
Telephone 548-222.

Overseas representatives

UNITED KINGDOM AND EUROPE: MEDIA NET-
WORK EUROPE, 27 Wilfred Street, London, S.W.1.
Telex 28905. Telephone: 01-370-6269.

U.S.A. AND CANADA: S. S. KOPPE AND Co. INC., 10
Stuyvesant Ave., Lyndhurst, N.J. 07071, U.S.A.

AUSTRALIA: F. W. PUBLICATIONS, Suite 103, 84 Pitt
Street, Sydney 2000. Telephone: 231-5891

JAPAN: SUN-GAIN SHIA LTD., Tenroku Hankyu
Bldg., No. 5, 6 Chome Tenjinbashi-ji, Oyodo-ku,
Osaka.

Subscriptions

Post free: New Zealand \$15.00 per year; overseas
\$23.00 per year.

Microfilm

Microfilms of *New Zealand Engineering* are available
from University Microfilms Inc., 300 North Zeeb
Road, Ann Arbor, Michigan 48106, U.S.A.

NZ ISSN 0028-808X

Leading article

The advancement of engineering science..... 197

Papers and articles

Victorian building reinstated: ANZ Bank, Dunedin. . *David G. Cox* 198

Newnham Lecture, *James F. Duncan* 203

Reservoir sedimentation in the Rangitaiki River
R. A. Callander and J. N. Duder 208

General

Conferences and courses 207

N.Z.I.E. news 216

Consultants' notebook 218

Changes in roll 219


Obituary 220

Candidates for election 220

MEMBER
BUSINESS PRESS **BPA** ASSOCIATION

Cover picture

The ANZ Bank building in Dunedin, built in 1874, after renovation and strengthening as described in the paper on p. 198.



Fenner V-Belts...

A reputation built on forty
years of international leadership

Founded in 1861, Fenner has been a driving force in the power transmission field for more than 100 years. We have been building V-Belts for forty of these. Ever since the pioneering days when the short-centred V-Drive began to take over from the line shaft. For most of this time we have also produced the pulleys and bushes which complete the drive package. Which means we are engineers with a thorough grasp of power transmission problems - not just a V-Belt manufacturing company. You can consult Fenner on all

aspects of drive design. And if size is any measure of success, Fenner can now claim to be the largest producer of complete V-Belt drives in the world. It's a position we're proud of - and one which we mean to maintain. By making sure that the quality of our products and the service we offer our customers is the best in the business. The Fenner standard range of V-Belts includes over 400 sizes, embracing ISO, DIN and BS recommended lengths. Most of these are available ex-stock. Top quality compounds and

Terylene load carrying cords are used throughout. Any belt you buy with our name on it will be anti-static and resistant to oil, heat and fire. These are just a few of the facts about Fenner. It will pay you to find out more.

Fenner

Fenner International Limited
Marfleet
Hull HU9 5RA
England

Stockists appointed throughout main centres. Write for detailed information to the New Zealand distributors ...



**THE GENERAL
MACHINERY CO**
LIMITED

A member of the John Burns Group.

For more information circle No. 2 on reader service card.

HEAD OFFICE
TAUPO QUAY — WANGANUI
P.O. BOX 293 — PHONE 58-335
TELEGRAMS: "MILRIDGE"
TELEX: MILRIDGE NZ3037

Fast, accurate response to changes in signal pressure.

Pneumatic pressure actuated control valves for steam, water and other fluids.



Model V250UE with equal percentage plug.

Model V250UO with on-off plug.

In sizes from 1/2 in. to 2 in. Maximum allowable steam pressures up to 200 p.s.i.

Both models are effective for low pressure, non-critical control systems where capacity to demand ratio is high.

Model V250UO should be used in applications in which demand alternates between no flow and full flow, and is excellent for steam, water and other fluids.

Equal Percentage Plug for high capacity service has stem guiding for greater stability at high flow.

On-Off Plug for dependable, quick opening action uses a special taper plug that exposes full flow area with short lifts.

Metal Seating ensures precision mating with shutoff tight enough for the majority of uses.

Rugged Construction and Enhanced Corrosion Resistance Foxboro P-Series, vinyl-coated, die-cast aluminium diaphragm actuator provides fast, accurate response. (Reversible by inverting topworks on yoke.) Vinyl coating and enclosed spring increase corrosion resistance. Guided by Teflon plastic faced bronze/steel bushings. Low friction seals for minimum hysteresis. Preformed Neoprene plastic/nylon diaphragm retains constant area through full stroke. Valve body is cast bronze and rated at 250 p.s.i. at 220°C.

These valves are available in a variety of specifications and with various optional extra controls.

Write for full specifications to

Manufactured in New Zealand by:




W. Arthur Fisher Ltd

Auckland: P.O. Box 12-747, Penrose, Phone 692-629
 New Plymouth: P.O. Box 514, Phone 88-128
 Wellington: P.O. Box 30-951, Lower Hutt, Phone 694-702
 Christchurch: P.O. Box 4158, Phone 67-692



New Zealand Made

34666



You'd be surprised what some people do with our angles and channels!

We sell a lot of angles and channels and we don't know where they all go. Some uses are obvious - for demountable partitioning, shelving supports, angle bracing in house construction and ducting in buildings. But some of our customers surprise us in their ingenuity. The Dairy Board, for instance, had problems trying to make a suitable large package to protect their bulk butter in transit: Now they use our angles on corners and it's just the job - light yet rigid. Maybe our standard angles and channels (and they come in many sizes and gauges) will provide the answer to your present problem? You never know 'til you think about it. By the way, being drawn, not press-brake, our angles and channels have no limit to length and our prices are very favourable particularly on quantity lots. Contact us in your area. We're in the yellow pages. We'll help you work something out



Above — The N.Z. Dairy Board bulk packages strengthened with Dimond angles



Top — Inexpensive and light barbecue legs.

Below, right — used to make a mudscraper.

Below, left — as garden stakes.



DIMOND ANGLES & CHANNELS

THE BUILDING BLOCKS OF METAL CONSTRUCTION



ALL DIMOND PRODUCTS ARE MARKETED THROUGH WINSTONE LTD.

7304

For more information circle No. 4 on reader service card.

Graphs into Numbers

with the HP9874A digitizer



Whenever your graphic information must be converted into numeric form, the 9874 Digitizer makes the job easy. Digitizing makes analysis of strip-chart recordings easy and automatic. Electrocardiograms are examples of raw data that are commonly recorded on strip charts. Point locations along the charts are measured, converted into digital form and entered into a computer. The 9874 is faster and more accurate than manually measuring each point location and entering it into your computer through the keyboard. You can digitize recordings up to 53 kilometres long.

With the 9874's rear projection and tiltable platen features, projectable media can be easily digitized. Just set a projector behind the digitizer and tilt the glass platen to the vertical position. The platen's front surface is treated so you can project exact images such as X-rays. Another sample application where the 9874's rear projection feature might be used is in left ventricular volume studies of the heart. Computer analysis of this digitized information can help determine whether a coronary bypass operation is necessary.

Cursor. The 9874's free cursor gives you pinpoint precision. Its open-circle target, .250mm (0.010 in.) in diameter, allows you to accurately position the cursor over a line thinner than a human hair. The two switches on the cursor are the digitize switch and the vacuum switch.

Compatibility. System 45, Hewlett-Packard's powerful graphic desktop computer is an ideal partner for the 9874. It puts graphics, enhanced BASIC language, typewriter keyboard, optional thermal printer, CRT display and high-performance.



AUCKLAND 56 9651

WELLINGTON 87 7199



Sales & Service from 172 offices in 65 countries.

To: Hewlett-Packard (N.Z.) Ltd.,
4-12 Cruickshank Street Kilbirnie, Wellington 3.

Please send me additional information on the 9874A

Name

Position

Organisation

Address

Phone

M.C. JB02/N.Z.

For more information circle No. 5 on reader service card.



technical information from the UK

Are you interested in the UK for the importing of products? These detailed buyers guides to the UK Engineering industry are a must for those involved in purchasing, design or market research.

Don't re-invent the wheel at your plant with costly "one-off" designs, find out the alternatives.

Don't waste valuable time tramping around the UK finding agencies. Do your market research from the comfort of your own office. Plan that trip by picking the products from these Directories,

get the vendors name

then telex or phone them to see if an agent already exists. Save dollars, time is money. Fill in the coupon for immediate information at your fingertips.



PLEASE SEND ONE YEAR'S SUPPLY (2 ISSUES) OF THE FOLLOWING PRODUCT DATA BOOKS.

- Chemical Engineering Index \$65.50
- Electronic Engineering Index.. .. . \$65.50
- Engineering Components & Materials Index .. \$65.50
- Manufacturing & Materials Handling Index .. \$65.50
- Laboratory Equipment Index (1 issue only) .. \$37.50

Name

Title Company

Address

.....

City State Post code.....

ALL CORRESPONDENCE TO:
Technical Publications Ltd
P.O. BOX 3047, WELLINGTON, N.Z.

The **RAWLPLUG** Check List

every name you need in fixing devices



Our famous name has led us to be slightly misunderstood. The brand name Rawlplug has become generic. OK, so we're the first name that comes to mind when you think of Rawlplugs as such. But there's a lot more behind our famous brand name.

Rawlplug stands for a total range of fixing devices. Each of them has a specific product name. Together they provide every conceivable fixing device requirement. Use the Rawlplug check list as an essential specifying reference. Ask for these products by name and you've got all the support you need.



EXPANDITE LIMITED, Head Office P.O. Box 38-079 Petone, Phone 688-046
 P.O. Box 494 Auckland, Phone 600-711, P.O. Box 9077 Hamilton, Phone 80-162
 P.O. Box 1406 Palmerston North, Phone 70-229, P.O. Box 45013 Eparua, Lower Hutt, Phone 687-965,
 P.O. Box 4190 Christchurch, Phone 68-194, P.O. Box 14-14 Dunedin, Phone 87-003.
 Telegrams EXPANJOINT.




For more information circle No. 7 on reader service card.

CASTING

Amazing the things you can cast from aluminium ingots

Aluminium has unique cast-ability. It precisely forms even the most intricate shape. Before you make your choice of casting material, get the full — and fascinating — technical details.



COMALCO
is aluminium

3.9

For more information circle No. 8 on reader service card.




Specialized construction services

engineered post-tensioning



leaders in the field of

REMEDIAL ENGINEERING



UNPRECEDENTED ENGINEERING EXPERTISE

- 1 The SCB Process of controlled pressure injection with epoxy resin has been carried out underwater at depths of 50m on some of the worlds largest concrete structures – the North Sea oil platforms.
- 2 The SCB Process has been used to reinstate earthquake damaged structures such as the Taueru Bridge in Masterton.
- 3 The SCB repair method provides full strength repair to cracked concrete and prevents the ingress of corrosion promoting moisture.
- 4 SCB licences in 52 countries have restored decaying architectural features on many notable buildings while at the same time improving their structural integrity.
- 5 Steel plates bonded to concrete beams and slabs using specially formulated epoxies have greatly extended the life of many European (and U.S.) bridges.
- 6 & 7 Equipment and expertise are immediately available to design, install and operate hydraulic lifting operations of all kinds. The above photos show the lifting of 30 storey cover slabs for an office block in Sabah (East Malaysia).
- 8 The Fabriform process offers a neat and economical solution to repair of timber, concrete and steel structures both above and below water level.

We thrive on solving your problems

Technical Engineering Development & Export Co. Ltd
BBR New Zealand Ltd

P.O. Box 473 Masterton or P.O. Box 51-391 Auckland
Tel 83-450 Masterton Tel 49-259 Papatotoetoe



Are you interested in the Australian marketplace for engineering and electronic products?

The Australian Engineering Directory is without doubt the most comprehensive and up-to-date source of information on the Engineering Industry ever published in Australia, and, like previous issues, will be an essential tool for anyone involved in engineering design, specification or procurement.

For the statistically minded, the 486 page Directory lists 873 Australian companies manufacturing or supplying engineering components and equipment, classifies their products under 2295 product headings, and lists the Australian agents for over 7000 overseas companies and trade names.

The Australian Electronics Directory lists over 450 Australian suppliers with their interstate offices and distributors and the names of key executives, classifies their products under more than 1600 product headings, fully cross-referenced and lists the local distributors for over 3600 overseas companies and trade names.

Are you interested in exporting to Australia? Selecting an agent? Evaluating the market and the competition? Save thousands of pounds on travel and executive time lost in another country. A small investment brings you these answers.



TECHNICAL PUBLICATIONS LTD. P.O. BOX 3047, WELLINGTON 1, NEW ZEALAND

Please supply the "Australian Engineering Directory" by surface mail	at NZ\$63.25
Please supply the "Australian Engineering Directory" by airmail	at NZ\$75.25
Please supply the "Australian Electronics Directory" by surface mail	at NZ\$63.25
Please supply the "Australian Electronics Directory" by airmail	at NZ\$75.25

(Delete whatever is not required)

Remittance enclosed.


Please bill.

Name

Address

.....

This Symbol



is your guarantee of Strength & Quality
for engineered timber trusses. Specify it!

Throughout New Zealand and the rest of the world, timber trusses manufactured with Gang-Nail truss connector plates are recognised by builders, architects and engineers for their superior quality.

Gang-Nail trusses are manufactured by licensed Fabricators to rigid standards with special high speed production equipment.

Gang-Nail Plates used exclusively by licensed Fabricators in their truss manufacturing are of patented design.

Get the best at a competitive price. Your Gang-Nail truss Fabricator is listed opposite.

Specify only genuine
GANG-NAIL
components



NORTHLAND

Carter Merchants (Northland) Ltd
Ph. 83-659 Whangarei.

Stewart Timber & Hardware Ltd
Ph. 89-159 Whangarei
Carter Merchants Ltd
Dargaville (Agent)
Carter Merchants Ltd
Kaikohe (Agent)

AUCKLAND

Carter Merchants (Maramara) Ltd
Ph. 299-9080 Papakura
Carter Merchants (Morningside) Ltd
Ph. 412-9714 Kumeu
Fletcher Timber Co.
Ph. 599-979 Auckland
Manukau Timber Co. Ltd
Ph. 661-169 Auckland
Neil Timber Ltd
Ph. 876-059 Auckland
Taupo Totara Timber Co.
Ph. 82-109 Papatotēke

WAIKATO

Bartholomew Timbers Ltd
Ph. 494-924 Hamilton
Odlin Limited
Ph. 79-112 Frankton
Taupo Totara Timber Co.
Ph. 7099 Putaruru

BAY OF PLENTY

Mount Timber & Hardware Ltd
Ph. 54-009 Mount Maunganui
Odlin Limited
Ph. 8359 Whakatane.

HAWKES BAY

Holt & Sons Ltd
Ph. 53-099 Napier
Holt & Sons Ltd
Ph. 88-099 Gisborne

TARANAKI

Boon Bros Ltd
Ph. 85-152 New Plymouth
W. J. Cleland & Sons Ltd
Ph. 80-869 New Plymouth

MANAWATU

Carter Merchants (Bassetts) Ltd
Ph. 54-134 Wanganui
Carter Merchants (Manawatu) Ltd
Ph. 89-029 Palmerston North
M.S.D. Speirs Ltd
Ph. 8944 Foxton

WELLINGTON

Fletcher Timber Co. Ltd
Ph. 8389 Tawa
Hutt Timber & Hardware Ltd
Ph. 673-109 Naenae, Lower Hutt.

NELSON/MARLBOROUGH

Nail Plate Trusses Nelson Ltd
Ph. 77-700 Nelson
F.L. Anderson Ltd
Ph. 83-099 Blenheim

CANTERBURY

Addington Timber Co.
Ph. 429-188 Christchurch
Fletcher Timber Co. Ltd
Ph. 45-109 Christchurch
Peter Stevens Ltd
Ph. 595-272 Christchurch
Fletcher Timber Co. Ltd
Ph. 82-109 Timaru

WESTLAND

Ngahere Processing Co.
Ph. 984 Ngahere

OTAGO

De Geest Bros. Construction Ltd
Ph. 71-172 Oamaru
Fletcher Timber Co. Ltd
Ph. 49-910 Oamaru
Fletcher Timber Co. Ltd
Ph. 770-953 Dunedin.

SOUTHLAND

Port Craig Timber Co. Ltd
Ph. 82-194 Invercargill



GANG-NAILS N.Z. LIMITED

P.O. Box 58-014, East Tamaki, Auckland

For more information circle No. 11 on reader service card.

**Behind the tap we all take for granted
is an essential commodity with
a technology of its own.**

**Water management to the Kent team
means
measuring and controlling supply and demand,
monitoring quality
and eliminating pollution.**

At the Auckland Regional Authority's Ardmore Filter Station Kent instruments are working in association with Portals Water Treatment (N.Z.) Ltd in a bulk water supply extension project. Kent Instrumentation and controls include flow meters, Deltapi E transmitters, Flexel indicators and controllers, EIL pH and fluoride monitors, Foster Cambridge P250L recorders, linked to a Kent K70 computer.



**In places from Jamaica to Jahore, Inverness to Invercargill the
Kent team of instruments and controls are working daily with engineers
in the management and treatment of ever-growing volumes of water
and waste water. Kent have only had 98 years to develop
solutions to the problems of many centuries.**

**With our programme of continuing product evaluation and
improvement we know we'll learn a lot more in the next 100 years.**

KENT INSTRUMENTS (N.Z) LTD.

HEAD OFFICE: P.O. Box 11-264, Auckland 5. Telephone 592-133; Telex NZ 21-265.
WELLINGTON: Telephone. TWA-7114 CHRISTCHURCH: Telephone 585-101
ALSO AT: Dunedin, Napier.

The advancement of engineering science

ACCORDING to our rules, advancement of engineering science is our primary goal. All our institutional organisation is orientated to it, be it qualification, practice, technical papers, standards activities, groups, divisions, branches, continuing education, engineer in society, or monitored training.

But are we "pursuing" the goal, driving forward? Is there a sharp edge to our endeavour, related to a clear perception that, at bottom, the only status and standing worth having rest on the quality of our performance as engineers.

From John Smeaton's "Society of Civil Engineers", founded more than 200 years ago, the institutions have existed to foster discussion "between men of practical science". The vehicle has been, mostly, the technical paper — a careful and thorough exposition, as befits an engineer, for the considered discussion of fellow engineers. Paper and discussion together provide the step forward, or the reference which will assist and benefit other engineers. Preparation of a paper is in itself a valuable experience in the arts of communication so essential to everyday work with the profession's clients.

The art of the technical paper seems now to be declining. Whether this is in spite of, or because of the amount of technical activity is not clear. Some of our technical groups meet for discussion. This is in the tradition. It advances engineering science, and provides the social benefit which should never be underestimated. It also provides immediacy, and our present problems may indeed have to

do with the stately and extended progress of a technical paper from preparation to branch presentation, to the reviews and decision-making of the publications committee, and on to annual conference and publication.

A discussion meeting is fine for those who are able to attend. Increasingly, the smaller, and particularly the more remote branches have become disadvantaged as the technical range of the large urban branch programmes has become elaborated by the developing activities of the technical groups.

What do we need to do, then? What changes do we need to make? The experience of the prepared technical paper, its record, its objects, benefits, communication, are all too good to be thrown away. Clearly we must re-establish the art. Let us solve the problems of immediacy, disadvantage, and sharing. Engineering science committee's current consideration of a decentralised programme committee to arrange a couple of well prepared and relevant papers, with the interests of the more remote branches in mind, may well have the right direction.

Immediacy, and sharing, are questions which can be addressed in the further working out of policy for the new trilogy of journal, transactions, and proceedings which will accompany the emergence of a new *New Zealand Engineering*. Thus, equipped anew, let us ensure that the path ahead continues to be at once tested and illuminated by the high standard of the individual technical contribution of members. ▽

* Unless specifically indicated, statements or opinions in *New Zealand Engineering* do not necessarily reflect the views of the Institution or the publishers. Correspondence on material published is welcome.

Victorian building reinstated

ANZ Bank, Dunedin

DAVID G. COX*

M.E., F.I.E. AUST. (FELLOW)

This original building, designed by R. A. Lawson, architect for many of Otago's notable early buildings, was built in Princes Street, Dunedin, in 1874. It is one of the finest examples of early Victorian architecture which has done much to influence the character of present-day Dunedin. It had been occupied continuously by the Union Bank, later to become the A.N.Z. Bank, for a century before being vacated to allow the recent reinstatement.

1. INTRODUCTION

THE exterior of light-coloured Oamaru stone cladding and dark grey Port Chalmers basalt base had generally weathered well, but the interior had deteriorated and the double-pitch internal valley slate roof and framing were in a poor state of repair. The first-floor ceiling showed evidence of severe water damage.

Furthermore, the construction of load-bearing masonry and timber floors offered poor seismic resistance. The original lime mortar, commonly used in early masonry construction, had deteriorated and calcified, with areas of local fretting and failure.

The structure exhibited some signs of cracking throughout, although the north and west walls were generally sound. Cracking was particularly severe in the rear or east wall, where the building is at its highest. This wall was virtually separated from the adjoining side walls owing largely to a lack of bonding around corners.

The existing layout was inefficient and ill suited to modern banking requirements. Recognition of this, together with its inferior structural condition, led the bank in the early 1970s to consider demolition and redevelopment in conjunction with the adjacent site to the east. Bank staff were very conscious of the quality of the building and its importance to Dunedin's heritage, but they were growing increasingly concerned at the risk to occupants under severe earthquake conditions, and also to pedestrians on adjacent footpaths.

When strengthening and renovation were first seriously considered as an alternative to demolition and redevelopment, the client queried the degree of upgrading which could reasonably be achieved in terms of modern seismic code requirements. Following a careful analysis of previous earthquakes in the Dunedin area which indicated a maximum felt intensity of MM5 in the previous 20 years, a preliminary examination of possible structural techniques was undertaken. On this basis, the client was advised that while avoidance of damage could not be guaranteed under moderate to severe earthquake conditions, it was considered that sufficient structural integrity could be achieved to ensure the safety of occupants and pedestrians in earthquakes up to approximately MM8. This was considered acceptable in view of the lower degree of seismic activity in the coastal Otago region (Zone C) compared with other more active parts of the country. It was further recognised that in the improbable event of an

earthquake of greater intensity than MM8 occurring within the extended life of the building, protection of staff and public could not be assured. However, the relative degree of risk would still be significantly less than for many other buildings throughout the city.

This proposed level of strengthening was in line with the then recent amendment to the Municipal Corporations Act (301A) which required building owners to upgrade existing buildings to at least 50% of current code loading requirements. This amendment had not in fact been adopted by the Dunedin City Corporation, but it was used as a basis for assessment and later discussions with the corporation.

In April 1974, Dunedin experienced its most severe earthquake for some 40 years, reaching a felt intensity of MM7. By coincidence, this occurred during the period when the feasibility of reinstatement was being examined. A subsequent detailed inspection revealed that the structure had suffered no obvious further damage, although some minor movements had occurred along the lines of existing cracks. This was most encouraging, and became a significant factor in the decision which was taken soon afterwards to proceed with reinstatement.

2. DEVELOPMENT OF STRENGTHENING SCHEME

In collaboration with the architects, Stephenson & Turner, a variety of alternative structural proposals for strengthening were investigated. One major constraint was the timber floor construction, since the code requirements



Fig. 1: Elevation from Princes Street.

* Principal, Brickell, Moss, Rankine & Hill, Consulting Engineers, Dunedin.

This project was awarded a Certificate of Merit in the 1978 A.C.E.N.Z. Merit Award Competition. It was first received for publication on 22 September 1978 and in its present form on 23 May 1979.



Fig. 2: Pediment and columns to front facade.

for fire-resistance limited such construction to two storeys only in the central commercial zone. It was considered neither practical nor economic to introduce fire-rated concrete floor slabs into the existing building, with corresponding extra supporting structure. This would also have added further heavy loads to be catered for, which was in turn undesirable. Since the area of the combined sites approached the maximum code limitation for this type of fire compartment, it was agreed to maintain the basement and ground floors only of the existing building, extending these levels into a new extension on the adjacent site. Thus the existing first floor could not be reused, which proved to be a distinct structural advantage, allowing loads to be reduced at that upper level, and making available the full height of the upper storey for part of the strengthening system.

Some additional floor area was required by the client at a later stage in the design development, and this was accommodated by including a limited area mezzanine between ground and first floor levels. This provided an additional intermediate level which could be utilised to obtain extra support to front and side walls. It had been decided at an early stage to demolish the rear east wall, since it was obviously beyond reinstatement.

The ground floor was in reasonable condition, requiring only local strengthening and an integration of local stiffening members.

Internal walls below ground level were generally load-bearing brick, and these, combined with the heavy basalt walls externally, indicated that the structure could be considered relatively stiff over this lower storey. Architectural requirements necessitated partial removal of two of these internal walls.

Particular hazards were identified as:

- (1) The massive pediment overhanging the front facade in Princes Street.
- (2) The four free-standing columns beneath the pediment.
- (3) The parapet and cornice to the north and west elevations.

3. PHILOSOPHY OF DESIGN

The above architectural and client requirements, combined with preliminary structural aspects, established the outline parameters around which the eventual strengthening scheme was finalised.

The overall philosophy thus aimed at a practical and realistic reduction of earthquake risk, while at the same

time providing reasonable protection for occupants and public. It was emphasised that this could not be proven in precise mathematical terms, since finite and detailed calculations of the ultimate strength of the building as a whole were considered to be of little practical value. Thus design concentrated on treating and stabilising particular hazards, reducing weight at upper levels, examining local elements and strengthening each of these in turn, and finally integrating all members into a bracing system to transfer loads eventually into the relatively massive and contained basement walls. The minimum basis required for specific calculations was 50% of the loads required by the then current code NZSS 1900:1965, Chapter 8, i.e., for Zone C, a seismic coefficient of 0.04. However, a coefficient of 0.08 was actually used, which, when multiplied by appropriate factors (2 to 6) when treating particular parts or portions, gave effective design coefficients ranging from 0.16 to 0.48.

4. OUTLINE OF FINAL SCHEME

The final scheme thus evolved comprised the following:

- (1) The removal and replacement of the existing roof concurrent with the construction of a steel-framed diaphragm at roof level, together with the bracing of higher level pediment, parapet and cornices. The new roof structure was placed considerably higher than the original roof to provide maximum possible support to higher level features.
- (2) The post-tensioning of the four front columns, front facade and pediment to achieve resistance to lateral seismic forces.
- (3) The provision of a braced steel diaphragm immediately above the existing first floor, together with vertical members bracing the full height of the upper storey and the roof space. Diagonal bracing then created deep, lightly framed steel trusses in both directions, thus acting as a fully braced space frame. Individual members adjacent to wall elements were fixed at close centres to steel dowels drilled and grouted to maximum depth into the walls behind. (See Figs. 7, 8.)
- (4) The reduction of all unnecessary heavy loads at higher levels.
- (5) The replacement of the existing cracked east wall with a new reinforced concrete frame dowelled into and tying together the side walls, while also providing a junction and seismic separation joint with the future new adjacent building. (See Fig. 3.)



Fig. 3: New frame to east wall nearing completion; replacement of parapet commenced.



Fig. 4: Internal view from mezzanine showing exposed steel after completion.

- (6) The construction of braced stiffening frames in precast reinforced concrete and structural steel inside the other three external walls.
- (7) The construction of a new mezzanine floor between existing ground floor and new first floor diaphragm levels, together with associated exposed steel stiffening members around remaining walls. This created an additional intermediate level of support, since all perimeter members were dowelled into adjacent wall elements.
- (8) The construction of a new concrete ring beam at ground floor level anchoring the base of precast wall columns, thus tying the whole system into floor and lower walls at ground level.
- (9) The provision of two stiff reinforced concrete portal frames replacing masonry walls in basement, removed to accommodate revised planning requirements.

5. PARTICULAR FEATURES, CONSTRUCTION ASPECTS

5.1 Pediment

This is large, heavy and partly overhangs Princes Street (see Fig. 2). It was possible neither to reduce the weight nor to remove any part of it without seriously detracting from the external appearance. Accordingly, steel RSJs were fixed to anchor dowels drilled in and grouted to maximum depth within the pediment itself at both upper and lower levels. Upper steel beams followed the triangular shape and were then firmly braced back into the new roof structure.

5.2 Columns to front facade

The four sculptured columns to the front colonnade were composed of several large blocks of Oamaru stone stacked one on top of the other. Thus the whole front facade, together with the pediment over, relied solely on gravity for stability (see Fig. 2).

Early ideas suggested drilling down through the centre of these into the basement buttress walls and post-stressing. This would have meant drilling some 13 to 15 m, maintaining precise verticality, while access at the top was extremely awkward. There was also the possibility of small steel dowels at the junctions of blocks which could have created severe disruptions to drilling operations.

This was discarded in favour of drilling down between columns and corresponding piers in the front wall. This

required only 600 to 900 mm of drilling through limestone at the top, and some 1800 to 2400 mm into basalt boulders in the basement buttress walls below. The need for precise verticality was not critical, and stressing cables could be more easily installed. Another major benefit was that the whole front facade was by this means effectively post-tensioned, further enhancing its overall lateral resistance. Large holes were opened up in the basement walls and dead end anchors concreted into anchor blocks. High tensile Freyssinet cables were then encased in steel pipes and sleeved through new upper level concrete beams cast into the rear of the pediment and over the front wall. They were later stressed from the top and left ungrouted for a period of more than 2 years to allow actual stresses to be checked prior to final grouting. In fact, relaxation in the central two columns averaged between 10 and 19%, and these were retensioned.

The level of prestress aimed at an average of at least 690 kPa over the whole area of column in front and pier behind. It was noticed when stressing approached this level in the central two columns that some minor cracking appeared in the flutes at joints. Originally it was assumed that all joints between blocks were fully bedded, but subsequent holes drilled into the joints proved they were only about one-third full around the outside. Thus high stresses were being concentrated around the outer edges, particularly to the flutes.

Stressing was partially relaxed while joints were grouted up, and although this was done under pressure it was not wholly successful. The surface area to be grouted in any one joint was large, with very dry adjacent stone surfaces. Despite presoaking with water through several holes, grout lost its moisture, and thus mobility, very quickly. It was estimated after grouting that joints were at least three-quarters full, and this was considered acceptable. Cracking was not significant to the two outer columns, largely owing to a greater spread of load with a corresponding lower level of effective prestress. Relaxation of stress in these was virtually negligible.

5.3 Parapet and cornice

Original design required the upper portion of the parapet to be removed to reduce height and weight, and the remainder dowelled with large-diameter deformed bars at close centres grouted into oversize holes drilled vertically down into solid masonry below the cornice. After the old roof had been removed it became apparent that some of the brickwork above the cornice was severely eroded and




Fig. 5: Mezzanine floor plan.

weathering away. Lime mortar was also severely fretted at this level. Cornice stones were held in place solely by the dead weight of the brick and stone above them, and they were showing some cracking. Thus the whole cornice and parapet were on the verge of instability.

It was quickly concluded that the existing parapet would have to be removed down to cornice level, but not until the outer edges of the cornice stones had been temporarily supported from exterior scaffolding. Vertical dowels were then grouted down into the lower level masonry as planned, and a new reinforced concrete parapet was formed and placed. This in turn meant that it was possible to return the new parapet to its original height, which was most acceptable architecturally. An added structural advantage was that the new concrete parapet around the front elevation anchored on to each end of the pediment and also served as the anchor beams for post-tensioning cables over the two end columns. In this way the pediment derived additional stability.

5.4 Steel space frame

Steel supporting columns from first floor to upper roof level were first anchored to dowels grouted into walls. The main N-S trusses were fabricated off-site in one piece, being some 16.5 m long by 5.8 m high. They were transported to the site during a weekend and erected with the tower crane, which was by that time fully operational. This was a distinct advantage over erection in sections.

Owing to the complexity of joints where up to 10 members coincided, the structural steel fabricator elected to site-weld all connections for members in an E-W direction. Original joint details required some bolted and some welded connections, but fully welded joints with all rectangular hollow section members were readily acceptable. Thus the upper levels became a fully welded, braced three-dimensional space frame.

5.5 Internal columns

Internal concrete columns to wall elements between windows from ground to first floor levels were originally planned to be placed *in situ*. However, the contractor requested that these be precast if possible. He advised that they would in fact be cheaper, since the confined working space made it very awkward to place concrete *in situ*. It was still essential that these be dowelled to the walls. Accordingly, sleeves were cast into the columns and corresponding dowels were grouted into the walls before precast columns were erected. These were done in two lifts

for ease of handling, the intermediate junctions being covered by main structural steelwork at mezzanine level. Plate washers were placed over the dowels in recesses in the column faces, welded all round, cut off and ground down, and recesses were then plastered. The locations of dowels are not now obvious without careful inspection.

6. CONTRACT CONSIDERATIONS

Naylor Love Construction Ltd, a local construction company, was selected as the contractor because of previous experience in the renovation of older buildings. The contract was negotiated on the basis of cost plus fixed fee, together with a total target price. Such work is highly labour-intensive, working within the constraints of existing structure and walls, and hence tends to attract higher than normal unit rates.

No specific construction difficulties were experienced apart from some of the inevitable unknowns connected with old buildings. It is essential to retain sufficient flexibility to modify details where necessitated by actual conditions once exposed. Likewise, a reasonable level of contingency is necessary for such contracts, since existing details often vary markedly from those indicated even on original drawings if these are still available.

The contractor elected to provide a tower crane on the adjacent site which proved far more satisfactory than frequent use of large mobile cranes operating from public thoroughfares. He also decided to retain the existing first floor until late in the contract period, which afforded him a convenient working platform for all upper level steelwork and roofing. This had the added structural advantage of providing some stability to external walls until the roof framing was virtually completed. (See Fig. 7.)

The overall scheme proved practicable and did not create unreasonable requirements of the contractor. It was recognised that this was a progressive upgrading and that, while each step added some strength locally, the scheme could not be considered satisfactory until all stages had been successfully completed. This is an inevitable consequence of this type of reinstatement. Local members or portions of the building may thus be more vulnerable over short periods, but when viewed in the light of a recent estimate that the return period for an earthquake of MM7 intensity in the Dunedin area is approximately 800 years,¹ it is a low risk. Consequently, the contractor was not required to go to elaborate lengths of temporary bracing for short periods until permanent members were fixed in place.




Fig. 6: First floor diaphragm plan.




Fig. 7: Section.